

Cleaning & Maintenance

Laminate

Use a clean, damp, non-abrasive cotton cloth and a mild liquid detergent or household cleaner for routine cleaning. Rinse with clean water using a clean, non-abrasive cotton cloth. Do not flood the laminate, especially near seams, since water can penetrate and cause the substrate to swell. Dry the surface with a soft, clean, non-abrasive cotton cloth.

Aluminum and Steel

These will be chrome-plated or powder coated and should be cleaned with a damp cloth. For a chromium-plated finish, to remove stains use a metal cleaner. We do not recommend the use of an abrasive cleaning agent.

Wood Finishes

Wipe with a damp cloth and buff with a soft duster for routine cleaning. Remove spills immediately with a slightly damp cloth.

Glass

We recommend a glass cleaning spray with lint-free cloths. Follow the manufacturer's instructions to assess its use and follow the recommended health and safety handling.

Leather & Fabric Upholstery

Please refer to manufacturer cleaning guidelines.

Polyester Felt

Please refer to manufacturer cleaning guidelines.

Carpet

We recommend proper routine vacuuming. For spills, remove as much of the excess spill as possible before using a clean cloth to blot spills and stains. Do not scrub and work from the outer edges inward to prevent spreading.

Minimize the risk of damage:

- Use coasters under glasses and hot mugs.
- Don't place potted plants on the surface unless kept in a watertight container; take extreme care when watering.
- Use protective pads under any equipment.
- Avoid overexposure to direct sunlight.
- Avoid exposure to excessive heat from a fire, radiator, or local high-temperature light sources.
- To avoid risks of fire or shock, always disconnect electrical power when cleaning products that use or provide electricity.
- Be careful not to allow liquids to enter any openings in electrical products.
- Under no circumstances should you use a silicon polish or wax.

Warranty

Orangebox warrants exclusively to the original purchaser of our product that all products (based on 8 hours of use per day) will be free from defects and structurally sound for 10 years from the date of manufacture, subject to exceptions.